

DC-D2212R

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Fixed-focal lens (f=4.0mm)
- micro SD / SDHC
- PoE (IEEE 802.3af Class 2), 12VDC
- Day and night (ICR)
- IR LED (Distance : 15m)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

VIDEO		
Image Sensor	1/2.9" CMOS	
Max. Resolution	1920 x 1080	
Scanning Mode	Progressive Scan	
Lens Type	Fixed-focal	
Focal Length	f=4.0mm	
Aperture	F2.0	
Iris Control	Fixed Iris	
Angular Field of View	84.4° (H), 50.3° (V), 104.6° (D)	
Pan / Tilt Range	Pan : -180° ~ 174°, Tilt : 0° ~ 65°	
Min. Illumination	Color : 0.07 Lux @ F2.0 B/W : 0 Lux (IR LED On)	
Dynamic Range	74.7dB	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter (1/7.5, 1/15)	
Day and Night	IR Cut Filter with Auto Switch	
IR Distance (LEDs)	15 m / 49.2 ft (2 ea)	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR	
Backlight Compensation	On / Off / HSBLC	
Image Stabilizer	-	
De-fog	-	
Privacy Masking	16 Zones	
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	
Video Out	1 BNC (Accessory)	
NETWORK		
	DirectIP Mode	Compatibility Mode
Video Compression	H.264 (MP), M-JPEG	
Intelligent Codec	-	
Bitrate Control	H.264 - CBR / VBR	
Audio Compression	-	
Two-way Audio	-	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Max. Frame Rate	30ips : 1920 x 1080	30ips : 1920 x 1080
Supported Resolution	1920 x 1080, 1280 x 720, 704 x 480, 640 x 360, 352 x 240	1920 x 1080, 1280 x 720, 704 x 480, 352 x 240
Multi-video Streaming	Quadruple Streaming	Triple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100 BASE-T)	
Recording Session Buffer	Yes (Up to 60MB)	
Edge Storage	micro SD / SDHC	
ALARM AND EVENT		
Trigger Event	Motion Detection, Tampering, Trip Zone	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	-	
Alarm In / Out	-	
ENVIRONMENTAL		
Vandal Proof Casing	-	
Outdoor Ready	-	
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting Up at Above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, PoE (IEEE 802.3af Class 2)	
Power Consumption	3.96W	
Approvals	FCC, CE, KC	
MECHANICAL		
Dimensions	Ø131mm x 79.3mm (Ø5.16" x 3.12")	
Weight	0.3kg (0.66lb)	

DIMENSIONS

(Unit - mm)



ACCESSORIES (OPTIONAL)



DA-WM2150

ACCESSORIES CONFIGURATION TREE

