

# Full HD 18x Flush PTZ Camera

## DC-S1263F

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- AF optical zoom lens(f=4.7 - 84.6mm), 18x zoom
- micro SD/SDHC
- Two-way audio
- Alarm in / out
- PoE(IEEE 802.3af class 3), 12V DC, 24V AC
- Day&night (ICR)
- Indoor enclosure
- Supports ONVIF



### SPECIFICATIONS

VIDEO		
Image Sensor	1/2.8" CMOS	
Max. Resolution	1920 x 1080	
Scanning Mode	Progressive Scan	
Lens type	AF Zoom Lens	
Focal Length	f=4.7 - 84.6mm	
Aperture	F1.6 - 2.8	
Iris Control	DC Auto Iris	
Angular Field of View	Wide : 61.2°(H), 35.6°(V), 68.9°(D) Tele : 3.6°(H), 2.1°(V), 4.1°(D)	
Min. Illumination	COLOR : 0.05 lux @ F1.6 B/W : 0.003 lux @ F1.6	
S/N Ratio	31.2dB	
Dynamic Range	74.7dB	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/8000), Anti-Flicker, Slow Shutter(1~1/5, 1/7.5, 1/15)	
Day & Night	IR cut filter with auto switch	
IR Distance (LEDs)	-	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR	
Backlight Compensation	On / Off / HSBLC	
Mirroring / Pivot	Horizontal / Vertical	
Image Stabilizer	-	
Privacy Masking	16 Zones	
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	
Video Out	1 Terminal Block	
Pan/Tilt/Rotate		
Pan Range	360° (Endless)	
Pan Speed	0.02~180°/sec (preset 420°/sec)	
Tilt Range	200° (-10~190°)	
Tilt Speed	0.02~180°/sec (preset 420°/sec)	
Preset	256ea	
NETWORK		
	<b>DirectIP Mode</b>	<b>Compatibility Mode</b>
Video Compression	H.264(MP), M-JPEG	
Video Compression Level (Quality)	Basic, Standard, High, Very High	
Bitrate Control	H.264 - CBR / VBR	
Max. Frame Rate	30fps : 1920 x 1080	
Audio Compression	G.726, G.711	
Two-way audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Supported Resolution	1920x1080, 1280x720, 704x480, 640x360, 352x240	1920x1080, 1280x720, 704x480, 352x240
Multi-Video Streaming	Quadruple streaming	Quadruple streaming
Network Protocols	Direct IP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-User Authority, IEEE 802.1x IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP™ NVR connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45(10/100BASE-T)	
Edge Storage	micro SD/SDHC	
ALARM & EVENT		
Trigger Event	Motion Detection, Alarm in, Audio detection, Tampering, TripZone	
Event Buffering (Pre & Post)	yes (up to 60MB)	
Event Notification	Remote S/W, Email (with Image)	
Audio In/ Out	Line-in 1ea / Line-out 1ea	
Alarm In/ Out	Input 1ea / Output 1ea	
ENVIRONMENTAL		
Vandal Resistance	-	
Out-door Ready	-	
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, 24VAC, PoE(IEEE 802.3af class 3)	
Power Consumption	DC12V : Max 10.6W / AC24V : Max 11.1W / PoE : Max 10.6W	
Approvals	FCC, CE(50130-4), KC	
MECHANICAL		
Dimensions	Ø226.5mm x 224.1mm (Ø8.92" x 8.83")	
Weight	2.2 kg (4.86 lb)	



### DIMENSIONS

(Unit - mm)



## DC-S1283FX

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- AF optical zoom lens (f=4.3 - 129mm), 30x zoom
- micro SD / SDHC, Smart Failover
- Two-way audio
- Alarm in / out
- PoE (IEEE 802.3af Class 3), 12VDC, 24VAC
- Day and night (ICR)
- WDR
- Low light enhancer
- Digital image stabilization
- Indoor enclosure
- Supports ONVIF



### SPECIFICATIONS

VIDEO		
Image Sensor	1/2.8" CMOS	
Max. Resolution	1920 x 1080	
Scanning Mode	Progressive Scan	
Lens Type	AF Zoom Lens	
Focal Length	f=4.3 - 129.0mm	
Aperture	F1.6 - 5.0	
Iris Control	DC Auto Iris	
Angular Field of View	Wide : 65.0° (H), 38.5° (V), 72.9° (D) Tele : 2.3° (H), 1.4° (V), 2.6° (D)	
Min. Illumination	Color : 0.01 Lux @ F1.6 B/W : 0.0004 Lux @ F1.6	
Dynamic Range	120dB (WDR)	
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10000), Anti-Flicker, Slow Shutter ( 1 ~ 1/5, 1/7.5, 1/15)	
Day and Night	IR Cut Filter with Auto Switch	
IR Distance (LEDs)	-	
Image Setting	Configurable Exposure, White Balance, Sharpness	
Digital Noise Reduction	Configurable 2DNR / 3DNR	
Backlight Compensation	-	
Mirroring / Pivot	Horizontal / Vertical	
Image Stabilizer	Yes (DIS)	
Privacy Masking	16 Zones	
Intelligent Video	Video Motion Detection, Face Detection, Active Tampering Alarm	
Video Out	1 Terminal Block	
PAN / TILT / ROTATE		
Pan Range	360° (Endless)	
Pan Speed	0.02 ~ 180°/sec (Preset 420°/sec)	
Tilt Range	200° (-10 ~ 190°)	
Tilt Speed	0.02 ~ 180°/sec (Preset 420°/sec)	
Preset	256ea	
NETWORK		
	<b>DirectIP Mode</b>	<b>Compatibility Mode</b>
Video Compression	H.264 (MP), M-JPEG	
Intelligent Codec	-	
Bitrate Control	H.264 - VBR	
Audio Compression	G.726, G.711	
Two-way Audio	Yes	
IP Camera Protocol	DirectIP	IDIS ONVIF Profile S
Max. Frame Rate	30fps : 1920 x 1080(WDR)	30fps : 1920 x 1080(WDR)
Supported Resolution	1920 x 1080, 1280 x 720, 704 x 480, 640 x 360, 352 x 240	1920 x 1080, 1280 x 720, 704 x 480, 352 x 240
Multi-video Streaming	Quadruple Streaming	Quadruple Streaming
Network Protocols	DirectIP Protocol	RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SNTP, SMTP, FEN, mDNS, uPNP
Security	SSL Encryption	Multi-user Authority, IEEE 802.1x, IP Filtering, HTTPS, SSL Encryption
Remote Access Client	DirectIP NVR Connection	IDIS Web, IDIS Mobile, IDIS Solution Suite
Ethernet	RJ45 (10/100 BASE-T)	
Recording Session Buffer	Yes (Up to 60MB)	
Edge Storage	micro SD / SDHC, Smart Failover	
ALARM AND EVENT		
Trigger Event	Motion Detection, Face Detection, Alarm In, Tampering	
Event Notification	Remote S/W, Email (With Image)	
Audio In / Out	Line-in 1ea / Line-out 1ea	
Alarm In / Out	Input 1ea / Output 1ea	
ENVIRONMENTAL		
Vandal Proof Casing	-	
Outdoor Ready	-	
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting Up at Above 0°C (32°F)	
Operating Humidity	0% ~ 90%	
ELECTRICAL		
Power Source	12VDC, 24VAC, PoE (IEEE 802.3af Class 3)	
Power Consumption	DC12V : Max 10.6W / AC24V : Max 11.0W / PoE : Max 10.5W	
Approvals	FCC, CE(50130-4), KC, UL	
MECHANICAL		
Dimensions	Ø226.5mm x 224.1mm (Ø8.92" x 8.83")	
Weight	2.2kg (4.86lb)	

### DIMENSIONS

(Unit - mm)

