

DP-DD1316

DirectIP™ 16-channel Decoder



- Supports IDIS IP Camera
- Supports HDMI, VGA, CVBS port
- Supports 4K Display (HDMI)
- Up to 480ips Live Display

SPECIFICATIONS

Video	
Video Inputs	16 IP Channels
Max. Resolution	Up to 12MP (Depending on IP Camera)
Supported Device	IDIS IP Camera
Video Outputs	1 HDMI, 1 VGA, 1 CVBS
Display Resolution	HDMI : 3840x2160, 1920x1200, 1920x1080, 1680x1050, 1600x1200 VGA : 1920x1200, 1920x1080, 1680x1050, 1600x1200 CVBS : 720x480(NTSC) , 720x576(PAL)
Display Speed	Up to 480ips
Network	
Video Compression	H.265, H.264
Max. Incoming Throughput	90Mbps
Ethernet	Gigabit Ethernet x1
Environmental	
Operating Temperature	0°C ~ +40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	12VDC, PoE
Power Consumption	12V±, 1.4A, 16.8W PoE, IEEE 802.3at(Class 4)
Approval	FCC, CE, KC
Mechanical	
Dimensions	200mm x 44mm x 153mm (7.9" x 1.7" x 6.0")
Weight	0.78kg (1.72lb)



PRODUCT IMAGE



DIMENSIONS

Unit - mm (inch)

