

DP-HE1201

HDMI/VGA Video Encoder



- Ease integration with 3rd party system
 - Quadruple Streaming
- Supports HDMI and VGA input ports
 - Supports 3840 x 2160 resolutions
- Remote Mouse and Keyboard Control through USB interface

SPECIFICATIONS

Video	
Video Inputs	1 HDMI, 1 VGA
Max. Resolution	3840 x 2160
Network	
Video Compression	H.265, H.264 (MP), M-JPEG
Max. Frame Rate	30ips : 3840 x 2160
Supported Resolution	3840x2160, 1920x1080, 1280x720, 704x480, 640x360
Multi-video Streaming	Quadruple Streaming
Ethernet	RJ45 (10/100BASE-T)
Alarm and Event	
Trigger Event	Motion Detection, Audio detection, Tampering, Trip Zone
Event Notification	Remote S/W, Email (with Image)
Interface	
Audio In / Out	1 / 1
USB	1 USB type B (Remote mouse and keyboard control)
Environmental	
Operating Temperature	0°C ~ +40°C (32°F ~ +104°F)
Operating Humidity	0% ~ 90%
Electrical	
Power Source	12VDC, PoE (IEEE 802.3af Class 3)
Power Consumption	12V= 0.95A, 11.4W PoE, IEEE 802.3af(Class 3)
Approval	FCC, CE, KC
Mechanical	
Dimensions	200mm x 44mm x 152.3mm (7.9" x 1.7" x 6.0")
Weight	0.8kg (1.76lb)



PRODUCT IMAGE



DIMENSIONS

Unit - mm (inch)



